



LAN / Ethernet Cable

Cat5e to Cat8 twisted-pair network cable - UTP to armoured S/FTP, indoor and outdoor. Every reel Fluke link-tested before shipping; CE / ISO 9001 / RoHS and GQT third-party reports supplied with your shipment.

- Fluke Link Test
- CE
- ISO 9001
- RoHS
- GQT Report

Key specifications

CATEGORIES	Cat5e / Cat6 / Cat6a / Cat7 / Cat8
CONDUCTOR	Oxygen-free copper / CCA
SPEED	100M / 1G / 10G+
STANDARD LENGTH	305m (1,000ft) pull-out box
JACKET	PVC / LSZH - indoor & outdoor
MOQ	Trial orders from 1 box - mixed containers welcome

Technical parameters

CONDUCTOR	Pure oxygen-free copper / copper-clad aluminium / bare copper
INSULATION	Polyethylene (PE)
JACKET	PVC - LSZH option available
SPEED RATING	100 Mbps / 1 Gbps / 10 Gbps+
SHIELDING	UTP / FTP / SFTP / U-FTP / S-FTP / armoured
INSTALLATION	Indoor, outdoor, duct & direct burial (armoured)
TESTING	Fluke channel / link test per batch, report supplied

23 constructions across Cat5e-Cat8

CAT5E - 4-PAIR TWISTED (9)	Indoor UTP / FTP / SFTP - Outdoor UTP / SFTP - Indoor & outdoor armoured SFTP - LSZH - Flame-retardant
CAT6 - 4-PAIR TWISTED (9)	Indoor UTP / FTP / SFTP - Outdoor UTP / SFTP - Outdoor armoured UTP / FTP - LSZH - Flame-retardant
CAT6A (3)	Indoor UTP with spline - Indoor U/FTP pair-shielded - LSZH
CAT7 / CAT8 (2)	Indoor S/FTP pair-shielded - LSZH

Packaging & logistics

STANDARD LENGTH	305m (1,000ft) per pull-out box
CUSTOM LENGTHS	100m / 200m / 500m on request
PRIVATE LABEL	OEM box print, jacket print & label supported
EXPORT PACKING	Cartons palletised, container-loading plan supplied
INCOTERMS	FOB / CIF / DDP - sea freight; DHL/UPS/FedEx samples

Send us your enquiry link in 10 hours. Mon-Sat